

GALLERY

COLLECTION



DOLOMITE



DOLOMITE



STATUARIO



STATUARIO



CALACATTA GOLD




CALACATTA GOLD



CARRARA

GALLERY

24"x48" 24"x24" 12"x24" 4"x12"



24"x48" . 60x120 cm 24"x24" . 60x60 cm



12"x24" . 30x60 cm 4"x12" . 10x30 cm

Glazed Porcelain Stoneware
Rectified Collection

ANSI A 137.1 compliant



WALL / FLOOR



MODERATE



0.34 in
8.5 mm



ASTM C 1026
RESISTANT



ASTM C 373
~0.1%



ASTM C 650: CLASS A
ASTM C 1378: CLASS A



ANSI A 326.3-2017 release 2019.
(ICOP): ≥0,42



HEAVY USE



Statuario Bianco



Calacatta Gold



Carrara



Dolomite

Sizes	Pieces					
		Sq.Ft.	Lbs.	Boxes	Sq.Ft.	Lbs.
24"x48"	2	15.50	61.00	36	558.00	2236.00
24"x24"	6	23.25	91.50	24	558.00	2236.00
12"x24"	8	15.50	61.40	32	496.00	1932.48
4"x12"	36	11.65	46.45	40	466.00	1858.00
12"x12" mosaic	10	9.70	-	-	-	-
10"x12" hexagon	10	10.71	-	-	-	-
4"x24" bullnose	10	-	-	-	-	-

*Indicates Special Order-Lead Time 2 Weeks

GALLERY

Dolomite

24"x48" 24"x24" 12"x24" 4"x12"



80NA05R
NA05 Dolomite Rect.
24"x48" . 60x120 cm



60NA05R
NA05 Dolomite Rect.
24"x24" . 60x60 cm



63NA05R
NA05 Dolomite Rect.
12"x24" . 30x60 cm



30NA05
NA05 Dolomite
4"x12" . 10x30 cm



32NA05MO
NA05 Dolomite Mosaic
1.4"x1.4" . 3x3 cm
(sheet 12"x12" . 30x30 cm)



32NA05HEX
NA05 Dolomite Hexagon
4"x4" . 10x10 cm
(sheet 10"x12" . 26x30 cm)



13NA05
NA05 Dolomite Bullnose
4"x24" . 10x60 cm



*Indicates Special Order-Lead Time 2 Weeks

GALLERY

Statuario Bianco

24"x48" 24"x24" 12"x24" 4"x12"



80NA10R
NA10 Statuario Bianco Rect.
24"x48" . 60x120 cm



60NA10R
NA10 Statuario Bianco Rect.
24"x24" . 60x60 cm



63NA10R
NA10 Statuario Bianco Rect.
12"x24" . 30x60 cm



30NA10
NA10 Statuario Bianco
4"x12" . 10x30 cm



32NA10MO
NA10 Statuario Bianco Mosaic
1.4"x1.4" . 3x3 cm
(sheet 12"x12" . 30x30 cm)



32NA10HEX
NA10 Statuario Bianco Hexagon
4"x4" . 10x10 cm
(sheet 10"x12" . 26x30 cm)



13NA10
NA10 Statuario Bianco Bullnose
4"x24" . 10x60 cm



*Indicates Special Order-Lead Time 2 Weeks

GALLERY

Carrara

24"x48" 24"x24" 12"x24" 4"x12"



80NA20R
NA20 Carrara Rect.
24"x48" . 60x120 cm



60NA20R
NA20 Carrara Rect.
24"x24" . 60x60 cm



63NA20R
NA20 Carrara Rect.
12"x24" . 30x60 cm



30NA20
NA20 Carrara
4"x12" . 10x30 cm



32NA20MO
NA20 Carrara Mosaic
1.4"x1.4" . 3x3 cm
(sheet 12"x12" . 30x30 cm)



32NA20HEX
NA20 Carrara Hexagon
4"x4" . 10x10 cm
(sheet 10"x12" . 26x30 cm)



13NA20
NA20 Carrara Bullnose
4"x24" . 10x60 cm



*Indicates Special Order-Lead Time 2 Weeks

GALLERY

Calacatta Gold

24"x48" 24"x24" 12"x24" 4"x12"



80NA07R
NA07 Calacatta Gold Rect.
24"x48" . 60x120 cm



60NA07R
NA07 Calacatta Gold Rect.
24"x24" . 60x60 cm



63NA07R
NA07 Calacatta Gold Rect.
12"x24" . 30x60 cm



30NA07
NA07 Calacatta Gold
4"x12" . 10x30 cm



32NA07MO
NA07 Calacatta Gold Mosaic
1.4"x1.4" . 3x3 cm
(sheet 12"x12" . 30x30 cm)



32NA07HEX
NA07 Calacatta Gold Hexagon
4"x4" . 10x10 cm
(sheet 10"x12" . 26x30 cm)



13NA07
NA07 Calacatta Gold Bullnose
4"x24" . 10x60 cm



*Indicates Special Order-Lead Time 2 Weeks

Reference		Characteristics	Standard	Required values		DC USA Values:
Dimensional standard	Calibrated	Nominal Size	ASTM C499	± 3%		Comply
		Caliber Range	ASTM C499	± 0.5%	± 0.08 in	Comply
		Warpage Edge	ASTM C485	± 0.5%	± 0.07 in	Comply
		Warpage Diagonal	ASTM C485	± 0.5%	± 0.07 in	Comply
		Wedging	ASTM C502	± 0.5%	± 0.08 in	Comply
	Rectified	Nominal Size	ASTM C499	- 3%	+ 2%	Comply
		Caliber Range	ASTM C499	± 0.25%	± 0.03 in	Comply
		Warpage Edge	ASTM C485	± 0.4%	± 0.05 in	Comply
		Warpage Diagonal	ASTM C485	± 0.4%	± 0.07 in	Comply
		Wedging	ASTM C502	± 0.25%	± 0.03 in	Comply
Mechanical Standard	Thickness	ASTM C499	± 0.040 in		Comply	
	DEEP Abrasion	ASTM C1243	<175mm ³		~ 40 mm ³	
	Bond Strength	ASTM C482	≥ 50 psi		Comply	
	Water absorption	ASTM C373	Maximum 0.5%		~ 0.1%	
	Thermal shock resistance	ASTM C484	Pass		Comply	
	Chemical resistance	ASTM C650	Pass		Comply	
	Stain resistance	ASTM C1378	Pass		Comply	
	Breaking Strength	ASTM C648	≥ 275 lbf		Comply	
	Resistance to Freeze/Thaw cycling	ASTM C1026	As Reported		Comply	
	Scratch Hardness	Mohs	Declared value		Mohs ≥6	
		Fire reaction - floor	EN 13823	Not Required		A1fl class (No reaction)
		Fire reaction - wall	EN 13823	Not Required		A1 class (No reaction)
		VOC	No VOC			
	US Requirements	Dynamic coefficient of Friction DCOF	ANSI A326.3-2017 release 2019	Wet value ≥ 0.42	Nat	0.63